# Product Specifications For P1250-1

# **Generator Set Specifications**

Minimum Rating	1125 kVA / 900 kW
Maximum Rating	1250 kVA / 1000 kW
Emissions/Fuel Strategy	Fuel Optimised
50 Hz Prime	1125 kVA / 900 kW
50 Hz Standby	1250 kVA / 1000 kW
Frequency	50 Hz
Speed	1500 RPM
Voltage	220-415 Volts

# **Engine Specifications**

Engine Model	Perkins® 4008-30TAG3
Bore	160 mm (6.3 in)
Stroke	190 mm (7.5 in)
Governor Type	Electronic
Displacement	30.6l (1867.3 cu. in)
Compression Ratio	13.0:1

# P1250-1 Standard Equipment

## **Engine**

Air Cleaner
Engine filled with lubrication oil
Low Coolant Temperature Shutdown

Perkins 4000 Series 8 cylinder engine Electronic governor Engine mounted fuel/water separator Lube drain valve

### Cooling

Package mounted radiator
Coolant Drain Valve
Engine mounted battery charging alternator
Cooling System filled with Coolant mix
Charge air cooled

#### **Exhaust**

Industrial silencer

#### Fuel

**Fuel Cooler** 

#### **Alternator**

Leroy Somer

AREP Excitation

IP23 Protection

#### **Control Panel**

PowerWizard 1.1+

### Mounting

Base, Formed Steel with Single wall Fuel Tank Lifting points on base frame

## P1250-1 Optional Equipment

#### **Exhaust**

Industrial, Residential, Critical Silencers
Catalytic converters
Heat Exhangers
Special spark arrestor silencers/certification

#### **Alternator**

Quadrature Droop Kit
Anti-Condensation Heater and Panel Circuitry
Increased alternator ingress protection
HV alternators

### **Control Panels**

PowerWizard 2.1
easYgen-2500, 3200, 3500
ComAp
Deep Sea
Customer tailored PLC System
Remote monitoring
Increased Control Panel Ingress Protection
Stand alone ATI transfer panel

## Starting/Charging

Lead Acid battery
Dual and air starting systems

#### General

Upgrade to Standard Set for "CE" Certification
Sound attenuated enclosures
Spring, Seismic anti-vibration mounts
Customer witness test
Remote cooling
Coolant heater
4-Pole circuit breaker
Motorised circuit breaker
LV and HV switchgear